



T200 E ELLIPTICAL SECTION

Profile Geometry

Code	Span S	Rise R	Area	Periphery	Step	Plates	Top/Base		Sides	
							Rt	αt	Rc	αc
T200	m	m	m ²	m	m		m		m	
E/01	1.57	1.73	2.12	5.17	0.15	4	705	76.43	910	103.57
E/02	1.72	1.88	2.52	5.64	0.14	4	768	70.09	980	109.91
E/03	1.98	2.20	3.43	6.58	0.34	4	929	101.46	1200	78.54
E/04	2.13	2.36	3.94	7.05	0.32	4	990	95.18	1270	84.82
E/05	2.26	2.51	4.48	7.52	0.39	4	1063	101.38	1370	78.63
E/06	2.57	2.83	5.67	8.46	0.28	6	1169	80.60	1490	99.40
E/07	2.71	2.98	6.32	8.93	0.34	6	1249	86.26	1580	93.74
E/08	2.85	3.14	7.00	9.40	0.32	6	1303	82.67	1660	97.33
E/09	3.14	3.46	8.48	10.34	0.24	6	1390	67.80	1800	112.20
E/10	3.28	3.62	9.26	10.81	0.29	6	1473	73.14	1890	106.86
E/11	3.40	3.77	10.08	11.28	0.58	8	1597	101.18	2050	78.82
E/12	3.58	3.93	10.95	11.75	0.21	6	1555	60.61	2030	119.39
E/13	3.70	4.08	11.84	12.22	0.47	8	1704	86.93	2170	93.07
E/14	3.83	4.24	12.76	12.69	0.53	8	1775	91.03	2270	88.97
E/15	4.01	4.40	13.74	13.16	0.25	8	1755	61.37	2270	118.63
E/16	4.14	4.55	14.73	13.63	0.43	8	1884	78.59	2390	101.41
E/17	4.24	4.72	15.75	14.10	0.73	8	1992	101.41	2570	78.59
E/18	4.41	4.87	16.83	14.57	0.48	8	2008	80.46	2570	99.54
E/19	4.56	5.03	17.93	15.04	0.46	10	2072	78.00	2640	102.00
E/20	4.68	5.18	19.07	15.51	0.68	8	2176	92.82	2780	87.18
E/21	4.83	5.34	20.24	15.98	0.66	8	2238	90.24	2850	89.76
E/22	4.97	5.50	21.45	16.45	0.65	10	2293	88.09	2930	91.91
E/23	5.10	5.66	22.68	16.92	0.88	8	2392	101.31	3080	78.69
E/24	5.24	5.81	23.96	17.39	0.86	8	2453	98.79	3150	81.21
E/25	5.38	5.97	25.27	17.86	0.92	8	2526	101.28	3250	78.72
E/26	5.53	6.13	26.62	18.33	0.91	10	2587	98.89	3320	81.11
E/27	5.66	6.29	28.00	18.80	0.98	12	2653	101.49	3430	78.51
E/28	5.81	6.45	29.42	19.27	0.87	10	2703	94.63	3470	85.37
E/29	5.95	6.60	30.88	19.74	0.94	12	2775	97.03	3570	82.97
E/30	6.10	6.75	32.37	20.21	0.92	12	2844	94.69	3630	85.31
E/31	6.23	6.92	33.88	20.68	1.07	12	2921	101.43	3770	78.57
E/32	6.38	7.07	35.45	21.15	1.05	12	2988	99.14	3830	80.86
E/33	6.51	7.23	37.03	21.62	1.12	12	3054	101.40	3940	78.60
E/34	6.66	7.39	38.67	22.09	1.02	12	3104	95.42	3980	84.58
E/35	6.81	7.54	40.33	22.56	1.08	12	3183	97.29	4070	82.71