



T150 C CIRCULAR SECTION

Profile Geometry

Code	Diameter	Area	Periphery	Radius	Plates
T150	m	m ²	m	m	
C/01	1.43	1.61	4.50	0.72	3
C/02	1.51	1.79	4.75	0.76	3
C/03	1.59	1.98	5.00	0.80	3
C/04	1.67	2.19	5.25	0.84	3
C/05	1.75	2.40	5.50	0.88	3
C/06	1.83	2.63	5.75	0.92	3
C/07	1.91	2.86	6.00	0.96	3
C/08	1.99	3.11	6.25	1.00	3
C/09	2.07	3.36	6.50	1.04	3
C/10	2.15	3.63	6.75	1.08	3
C/11	2.23	3.90	7.00	1.12	3
C/12	2.31	4.19	7.25	1.16	3
C/13	2.39	4.48	7.50	1.20	3
C/14	2.47	4.79	7.75	1.24	4
C/15	2.55	5.10	8.00	1.28	4
C/16	2.63	5.43	8.25	1.32	4
C/17	2.71	5.77	8.50	1.36	4
C/18	2.79	6.11	8.75	1.40	4
C/19	2.87	6.47	9.00	1.44	4
C/20	2.95	6.83	9.25	1.48	4
C/21	3.03	7.21	9.50	1.52	4
C/22	3.11	7.59	9.75	1.56	4
C/23	3.18	7.94	10.00	1.59	4
C/24	3.26	8.34	10.25	1.63	5
C/25	3.34	8.76	10.50	1.67	5
C/26	3.42	9.18	10.75	1.71	5
C/27	3.50	9.62	11.00	1.75	5
C/28	3.58	10.00	11.25	1.79	5
C/29	3.66	10.50	11.50	1.83	5
C/30	3.74	10.90	11.75	1.87	5
C/31	3.82	11.40	12.00	1.91	5
C/32	3.90	11.90	12.25	1.95	5
C/33	3.98	12.40	12.50	1.99	5

Code	Diameter	Area	Periphery	Radius	Plates
T150 C	m	m ²	m	m	
C/34	4.06	12.9	12.75	2.00	6
C/35	4.14	13.4	13.00	2.07	6
C/36	4.22	13.9	13.25	2.11	6
C/37	4.30	14.5	13.50	2.15	6
C/38	4.38	15.0	13.75	2.19	6
C/39	4.46	15.6	14.00	2.23	6
C/40	4.54	16.1	14.25	2.27	6
C/41	4.62	16.7	14.50	2.31	6
C/42	4.70	17.3	14.75	2.35	6
C/43	4.78	17.9	15.00	2.39	6
C/44	4.86	18.5	15.25	2.43	7
C/45	4.94	19.1	15.50	2.47	7
C/46	5.02	19.7	15.75	2.51	7
C/47	5.10	20.4	16.00	2.55	7
C/48	5.18	21.0	16.25	2.59	7
C/49	5.25	21.6	16.50	2.63	7
C/50	5.33	22.3	16.75	2.67	7
C/51	5.41	22.9	17.00	2.71	7
C/52	5.49	23.6	17.25	2.75	7
C/53	5.57	24.3	17.50	2.79	7
C/54	5.65	25.0	17.75	2.83	8
C/55	5.73	25.7	18.00	2.87	8
C/56	5.81	26.5	18.25	2.91	8
C/57	5.89	27.2	18.50	2.95	8
C/58	5.97	27.9	18.75	2.99	8
C/59	6.05	28.7	19.00	3.03	8
C/60	6.13	29.5	19.25	3.07	8
C/61	6.21	30.2	19.50	3.11	8
C/62	6.29	31.0	19.75	3.15	8
C/63	6.37	31.8	20.00	3.19	8
C/64	6.45	32.6	20.25	3.23	9
C/65	6.53	33.4	20.50	3.27	9